



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

[Document Change History](#)

12/14/2025

Contents

- 1 Document Change History
 - 1.1 8.1.400.30
 - 1.2 8.1.400.26
 - 1.3 8.1.400.24
 - 1.4 8.1.400.21
 - 1.5 8.1.400.17
 - 1.6 8.1.400.15
 - 1.7 8.1.400.12

Document Change History

As described in the ORS 8.1.4 Release Note, the following topics are new or have been updated.

8.1.400.30

The ORS REST API POST method for starting a new SCXML session now supports `application/json` as a new value for Content-Type.

8.1.400.26

ORS now supports URLs of lengths up to 4,094 bytes. Previously, ORS truncated URLs longer than 2,048 bytes upon execution of the `<session:fetch>` action with the HTTP GET method.

8.1.400.24

This release introduces a new function, which allows you to retrieve the Orchestration Server version. `_genesys.session.getServerVersion`

Parameters: None

Return value type: STRING (version of Orchestration Server)

8.1.400.21

This release introduces a new `detach` attribute for the `<ixn:redirect>` action. Please see the release note for more information.

8.1.400.17

Previously, ORS allowed the function `_genesys.session.setOptions` to override only eight options. This restriction is now removed.

8.1.400.15

If Transaction List item attributes are stored in non-string format and the

`_genesys.session.getListItemValue(list, item, key)` function retrieves the value of a particular key, it is returned as string. Previously, in this scenario, the `_genesys.session.getListItemValue()` function ignored non-string attributes.

Also, if `_genesys.session.getListItemValue()` is called with two arguments or with `*` as a third argument, the returned object will also include attributes whose values are empty strings. Previously, in ORS version 8.1.300.29, a minor defect was introduced, and attributes with empty values were not included in the returned object, when `_genesys.session.getListItemValue()` retrieved the Transaction List directly via ORS.

To provide a reason for a session not being able to control a session that it owns, this release adds a new `resultof` property to the `interaction.notcontrolled` event.

8.1.400.12

A new “urs” method is added to the `session:fetch` Action Element. It simplifies usage of Universal Routing Server functions, previously available for Orchestration Server only via the Universal Routing Server Web interface. See `<fetch>` under the [Action Elements](#) section.