



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

Fetch Data in JSON Format

12/12/2025

Fetch Data in JSON Format

As the following sample demonstrates, the fetched resource can return data in JSON format. The data can then be parsed by an SCXML session. Note that in this example the result of the parsing is stored in the Target global variable.

Fetches file content: File `http://localhost:9090/strategies/01_BASIC/_aux/GetDate.jsp`

```
<%= "{ \"year\":2008, \"month\": \"December\", \"date\":25} "%>
```

Root strategy

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:queue="www.genesyslab.com/modules/queue"
  xmlns:dialog="www.genesyslab.com/modules/dialog"
  xmlns:session="www.genesyslab.com/modules/session"
  initial="initial">
  <script>var date = ""</script>
  <state id="initial">
    <transition event="interaction.added" target="fetch"/>
  </state>
  <state id="fetch">
    <onentry>
      <script>var URI="http://localhost:9090/strategies/01_BASIC/_aux/GetDate.jsp";</script>
      <session:fetch srcexpr="URI" type="'application/json'"/>
    </onentry>
    <transition event="session.fetch.done" target="check">
      <script>date = JSON.parse(_event.data.content);</script>
    </transition>
    <transition event="error.session.fetch" target="error"/>
  </state>
  <state id="check" >
    <transition cond="date.month=='December' && date.date==25" target="routing"/>
    <transition target="error"/>
  </state>
  <state id="routing">
    <onentry>
      <queue:submit priority="5" timeout="20">
        <queue:targets type="dn">
          <queue:target name="'7102'"/>
        </queue:targets>
      </queue:submit>
    </onentry>
    <transition event="queue.submit.done" target="exit">
      <log expr="'DONE'"/>
      <log expr="_genesys.ixn.interactions[0].voice.ani"/>
      <log expr="'DONE'"/>
      <log expr="_event.data.targetselected"/>
    </transition>
    <transition event="error.queue.submit" target="error"/>
  </state>
  <final id="exit"/>
  <final id="error"/>
```

</scxml>