



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

Route to Agent and Run Treatments in Parallel

12/16/2025

Route to Agent and Run Treatments in Parallel

The SCXML strategy below demonstrates how to use parallel states. It applies a series of treatments while routing the interaction to an agent.

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:queue="www.genesyslab.com/modules/queue"
  xmlns:dialog="www.genesyslab.com/modules/dialog"
  initial="initial">
  <state id="initial">
    <transition event="interaction.added" target="routingwithdialog"/>
  </state>
  <parallel id="routingwithdialog">
    <state id="dialog" initial="prompt">
      <state id="prompt">
        <onentry>
          <dialog:play language="'English_US'">
            <dialog:prompts type="ann">
              <dialog:prompt interrupt="true" text="'You reached Genesys'"/>
            </dialog:prompts>
          </dialog:play>
        </onentry>
        <transition event="dialog.play.done" target="music"/>
        <transition event="error.dialog.play" target="error"/>
      </state>
      <state id="music">
        <onentry>
          <dialog:playsound type="'music'" resource="'MusicDN'"/>
        </onentry>
        <transition event="error.dialog.playsound" target="error"/>
      </state>
    </state>

    <state id="routing">
      <onentry>
        <queue:submit priority="5" timeout="80">
          <queue:targets>
            <queue:target type="agent" name="'az'"/>
          </queue:targets>
        </queue:submit>
      </onentry>
      <transition event="queue.submit.done" target="exit">
        <log expr="'DONE'"/>
        <log expr="_genesys.ixn.interactions[0].voice.ani"/>
        <log expr="'DONE'"/>
        <log expr="_event.data.targetselected"/>
      </transition>
      <transition event="error.queue.submit" target="error"/>
    </state>

  </parallel>
  <final id="exit"/>
  <final id="error"/>
</scxml>
```