



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

[Set User Data](#)

12/12/2025

Set User Data

The following SCXML strategy shows how to set and update user data for an interaction.

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:ixn="http://www.genesyslab.com/modules/interaction"
  initial="initial">

  <state id="initial">
    <transition event="interaction.added" target="setudata" >
      <script>
        _data.ixnid = _event.data.interactionid;
      </script>
    </transition>
  </state>
  <state id="setudata">
    <onentry>
      <script>
        var data = { details : { name : "Smith, John", age : 45 } };
        _genesys.ixn.setuData( data );
        _genesys.ixn.setuData( { category : 1 } );
      </script>
    </onentry>
    <transition target="update"/>
  </state>
  <state id="update">
    <onentry>
      <script>
        _genesys.ixn.setuData( { category : 2 }, _data.ixnid );
      </script>
    </onentry>
    <transition target="check"/>
  </state>

  <state id="check">
    <transition event="interaction.udata.changed"
      cond="_genesys.ixn.interactions[_data.ixnid].udata.category==2 &&
        _genesys.ixn.interactions[_data.ixnid].udata.details.name=='Smith, John' &&
        _genesys.ixn.interactions[_data.ixnid].udata.details.age==45"
      target="exit" />
    <transition target="error" />
  </state>
  <final id="exit"/>
  <final id="error"/>
</scxml>
```