

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services

Voice Treatment Section

Voice Treatment Section

- · treatment call failure answering mathiatment find agent fail
- _treatment_customer_connect_treatment_waiting_for_agent

_treatment_call_failure_answering_machine

Default Value:

Valid Values: String or as a JSON-formatted string

Changes Take Effect: Immediately

URI of the music file to play when a call is not answered by the customer and is forwarded to the answering machine. JSON-formatted strings can be used to specify hints to the RequestApplyTreatment.

The following example makes the music start playing after the answering machine beep is detected: { "file": "file url", "hints":{ "am-beep-detection":"on"} }

By default, the value of this option is empty and Callback uses the <GMS installation>/../Resources/SampleTreatments/call_fail_ans_machine.wav file from the Callback template.

To deactivate the play treatment, set the value of this option to { }.

treatment customer connect

Default Value:

Valid Values: String or as a JSON-formatted string

Changes Take Effect: Immediately

URI of the music file to play when the customer answers the callback.

The JSON-formatted strings can be used to specify hints to the RequestApplyTreatment. For example:

```
{ "file": "file url", "hints": {"hint1":"value"}}
```

_treatment_find_agent_fail

Default Value:

Valid Values: String or JSON-formatted string

Changes Take Effect: Immediately

Music file to be played when the service fails to find the agent in the time specified by the Max Time To Wait For Agent on the Call parameter. This parameter accepts a URI as a string or as a JSON-formatted string. See also _treatment_waiting_for_agent. By default, this option has an empty value and Callback will use the <GMS installation>/Resources/SampleTreatments/ all agents busy.wav file available in the callback template.

_treatment_waiting_for_agent

Default Value:

Valid Values: String or JSON-formatted string

Changes Take Effect: Immediately

Music file to play when the customer is waiting for an agent. This parameter accepts a URI as a string or as a JSON-formatted string. If you do not set this option, Callback will use the default <GMS installation>/Resources/SampleTreatments/next_customer_rep.wav file of the callback template.