



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Voice Platform

TalkerManager Section

## TalkerManager Section

- AckMsgFax
- AckMsgTDD
- EnableTDD
- HangUpAfterBlindXfer
- MinDownLoadSize
- RetryAllocResource
- TimeReconfigMFCMsec
- WaitAnswer2DTMF
- WaitFreeStatusDialOutMsec

### AckMsgFax

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Send ACK or NAK responses for each SIP INFO received in Fax operation.

### AckMsgTDD

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Send ACK or NAK responses for each SIP INFO received in TDD operation.

### EnableTDD

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Calls generated from TDD equipments will be accepted.

### HangUpAfterBlindXfer

**Default Value:** 1

**Valid Values:**

**Changes Take Effect:** After restart

Hangup call after blind transfer.

## MinDownloadSize

**Default Value:** 8192

**Valid Values:**

**Changes Take Effect:** After restart

MinDownloadSize in bytes

## RetryAllocResource

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Number of retries for waiting resources (-1==Forever, 0==Skip, 'n'==n\_times).

## TimeReconfigMFCMsec

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Time Reconfiguration MFC (msec)

## WaitAnswer2DTMF

**Default Value:** 1

**Valid Values:**

**Changes Take Effect:** After restart

Wait answer result before dialing DTMF.

## WaitFreeStatusDialOutMsec

**Default Value:** 0

**Valid Values:**

**Changes Take Effect:** After restart

Wait time for free status of dialout channel (msec)