



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition

routing-point-presence Section

12/17/2025

routing-point-presence Section

The routing point presence options enable agents to view routing point statistics information in Team Communicator. Refer to the [Enabling Team Communicator Calling Features](#) and [Enabling the E-Mail Channel](#) for information about how to use these options.

- [error-level](#)
- [statistic-name](#)
- [statistic-text](#)
- [warning-level](#)

For information about how to use these options to configure Genesys Web Services functionality and behavior, refer to the [Workspace Desktop Edition Deployment Guide](#).

error-level

Default Value: 10

Valid Values: An integer or a double value.

Changes Take Effect: When the application is started or restarted.

The value at which a statistic is considered to be at the upper threshold level.

statistic-name

Default Value: CurrNumberWaitingCalls

Valid Values: A valid name of a statistic server statistic queue.

Changes Take Effect: When the application is started or restarted.

The name of the statistic used to evaluate the presence for Routing Points.

statistic-text

Default Value: interaction(s) waiting.

Valid Values: Letters A to Z and a to z. Numbers 0 through 9. The underscore and space characters.

Changes Take Effect: When the application is started or restarted.

The text displayed beside the statistic value.

warning-level

Default Value: 5

Valid Values: An integer or a double value.

Changes Take Effect: When the application is started or restarted.

The value at which a statistic is considered to be at the warning level.