



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Skype for Business

connector section

12/17/2025

connector section

- `caching-enabled`
- `conference-pool-size`
- `reuse-avcall`
- `conf-session-shutdown`
- `musicOnHoldFilePath`
- `ringtone-file-path`

caching-enabled

Default Value: 1

Valid Values: 1, 0

Changes Take Effect: Immediately

Enables conference caching by default. Conference caching allows to reuse previously scheduled conferences. It reduces the load of Skype for Business Server and the time for establishing new calls. To disable conference caching, configure this option with a value of 0.

conf-session-shutdown

Default Value: false

Valid Values: true, false

Changes Take Effect: Immediately

Introduced: 8.5.001.11

If set to `true`, the Connector monitors the Conference Session state and will end the call if a Conference Session of this call goes to the Disconnected state. If set to `false`, the Connector does nothing in this situation.

conference-pool-size

Default Value: 0

Valid Values: 0-6000

Changes Take Effect: Immediately

Specifies how many conferences the connector creates and maintains in the pool for future use. Set the value to 20% higher than the maximum number of simultaneous calls handled by the connector.

musicOnHoldFilePath

Default Value: No default value
Valid Values: Any string
Changes Take Effect: Immediately

Specifies the path (full path, relative path or network path are supported) to the file with music that will be used as Music On Hold. The connector supports audio file .wma type.

reuse-avcall

Default Value: 0
Valid Values: Any positive integer
Changes Take Effect: Immediately

Specifies how many times the connector reuses an AudioVideo Call in different conversations, before releasing it to free memory. To eliminate a memory leak that can occur with excessive call reuse, however, set the option to a relatively low value, no greater than 50.

ringtone-file-path

Default Value: No default value
Valid Values: Any string
Changes Take Effect: Immediately
Introduced: 8.5.001.07

Specifies the path (full path, relative path or network path are supported) to the audio file that is played as a ringback tone to a caller while a call is alerting the receiving party. T-Server/Connector supports the audio file .wma type.