



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

UCMC Section

5/10/2025

UCMC Section

- `fips_enabled`
- `NotifyGMSDTMF`
- `RMAAddress`
- `UseSecureSIP`

fips_enabled

Default Value: False

Valid Values:

Changes Take Effect: After restart

This specifies whether to enable FIPS mode in UCMC. When FIPS mode is enabled, only FIPS 140-2 approved ciphers and algorithms can be used in SSL connections.

NotifyGMSDTMF

Default Value: false

Valid Values:

Changes Take Effect: After restart

This parameter specifies whether to enable the DTMF collection from GMS and notify it to CUCM TServer.

RMAAddress

Default Value:

Valid Values:

Changes Take Effect: After restart

IP Address and port information of the Resource Manager.(Eg: 10.10.10.10:5060)

UseSecureSIP

Default Value: false

Valid Values:

Changes Take Effect: After restart

This parameter specifies whether to use SIP over TLS instead of SIP. If this parameter is set to true, the RMAAddress parameter name may need to be changed to point to the SIPS port of RM