



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workforce Management

SMTP Section

12/15/2025

SMTP Section

- `AnonymousAccess`
- `Host`
- `timeout`
- `connectiontimeout`
- `Password`
- `User`
- `fromAddress`
- `Port`

AnonymousAccess

Default Value: false

Valid Values: true, false

Changes Take Effect: Immediately

Dependencies: None

Specifies whether or not WFM Daemon sends anonymous emails. If this option value is set to true WFM Daemon sends e-mails anonymously. If set to false WFM Daemon does not send e-mails anonymously.

connectiontimeout

Default Value: 60 seconds

Valid Values: Any positive integer

Changes Take Effect: Immediately

Dependencies: None

Introduced: 8.5.210.00

Specifies the time interval (in seconds) after which the connection between WFM Daemon and the SMTP server times out.

fromAddress

Default Value: " " (string)

Valid Values: Any valid e-mail address

Changes Take Effect: Immediately

Dependencies: None

Specifies the FROM e-mail address that is presented to users receiving notifications.

Host

Default Value: " " (string)
Valid Values: Any valid host name
Changes Take Effect: Immediately
Dependencies: None

This option is mandatory.

Specifies the host name of machine where the SMTP server is located.

Password

Default Value: " " (string)
Valid Values: Any valid password
Changes Take Effect: Immediately
Dependencies: None

Specifies the password that is used when connecting to the SMTP server. Set this option only if SMTP server requires connection authorization.

Port

Default Value: 25
Valid Values: Any positive integer
Changes Take Effect: Immediately
Dependencies: None

This option is mandatory.

Specifies the SMTP server port number.

timeout

Default Value: 60 seconds
Valid Values: Any positive integer
Changes Take Effect: Immediately
Dependencies: None
Introduced: 8.5.210.00

Specifies the time interval (in seconds) after which communication between WFM Daemon and the SMTP server times out.

User

Default Value: " " (string)
Valid Values: Any valid username

Changes Take Effect: Immediately
Dependencies: None

Specifies the username that is used to connect to the SMTP server. Set this option only if SMTP server requires connection authorization.