



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Performance Management Advisors Deployment Guide

Operation of Stat Server Redundant Pairs

12/16/2025

Operation of Stat Server Redundant Pairs

Genesys Adapter maintains connections to both the primary and the backup Stat Servers as long as they are available, and requests the historical statistics from both the Stat Servers of the pair at the same time.

For the purposes of Advisors Genesys Adapter, Primary and Backup are determined by the specified Adapter installation options. Primary and Backup, in this case, is not related to the Primary and Backup Stat Server designation in Configuration Manager.

So, when connection to the primary is lost, Genesys Adapter switches over transparently to receiving Stat Server updates from the backup Stat Server. The historical counts therefore remain the same even after the switchover.

After the first switchover, the configured backup Stat Server is now treated as the new primary Stat Server, but when the old primary server comes back online, no automatic switchover takes place. Instead, all the historical statistics are now requested from the old primary Stat Server.

Because this Stat Server has just come back online, it needs to be given sufficient time to accumulate historical aggregated statistic counts. Because in CCAdv, one-day metrics are used, there should be at least a day before the next switchover happens. If the switchover happens sooner, then those statistic values would be shown as aggregated from the time when the Stat Server came back online.