



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# T-Server Reference Guide

TMergeCalls

12/15/2025

---

## Contents

- 1 TMergeCalls
  - 1.1 Description
  - 1.2 Parameters
  - 1.3 Return Values

# TMergeCalls

## Description

On behalf of the telephony object specified by the parameter `dn`, merges the held call specified by the parameter `held_conn_id` with the active call specified by the parameter `current_conn_id` in a manner specified by the parameter `merge_type`. The resulting call will have the same `conn_id` as the held call.

## Parameters

Name	Description
<code>server</code>	Local server handle to the T-Server in question.
<code>dn</code>	Directory number of the telephony object on whose behalf the calls are merged.
<code>held_conn_id</code>	Connection identifier of the original call.
<code>current_conn_id</code>	Connection identifier of the active call.
<code>merge_type</code>	Specifies whether merging should result in a transferred or conferenced call. Refer to the type <b>TMergeType</b> .
<code>reasons</code>	A pointer to a data structure that provides additional information associated with this action.
<code>extensions</code>	A pointer to an additional data structure.

## Return Values

Standard (See [standard-return-values](#).)