



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

TSendEventEx

12/15/2025

Contents

- 1 TSendEventEx
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values
 - 1.4 Comments

TSendEventEx

Description

Sends the T-Library event specified by the parameter event to T-Server. This makes the data from the event available to the clients registered to receive events about the telephony object specified by the attribute ThisDn in the event. As distinct from the function TSendEvent(), this function also allows for a client specified by the parameter client_id to receive the event in question. (See below for details.)

Parameters

Name	Description
server	Local server handle to the T-Server in question.
event	A pointer to the data structure that should be sent. T-Server checks the contents of the data structure only to see if reference ID exists. When there exists a value for a reference ID, that attribute is passed only to the client specified by the parameter client_id. The remaining data structure is distributed both to that client and to the client(s) registered on the telephony object specified by the ThisDN attribute of the event in question.
client_id	Client identified for receipt of the data structure, including the reference ID, being sent.

Return Values

Standard (See standard-return-values.)

Comments

T-Server is not concerned with the contents of the user event.