



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

TUpdateUserData

12/12/2025

Contents

- 1 TUpdateUserData
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values
 - 1.4 Comments

TUpdateUserData

Description

On behalf of the telephony object specified by the parameter `dn`, updates the user data that is attached to the call specified by the parameter `conn_id` with the data specified by the parameter `user_data`.

Parameters

Name	Description
<code>server</code>	Local server handle to the T-Server in question.
<code>dn</code>	Directory number of the telephony object on whose behalf the information is to be updated.
<code>conn_id</code>	Connection identifier of the call in question.
<code>user_data</code>	A pointer to the user data that should be attached to the call.

Return Values

Standard (See `standard-return-values`.)

Comments

If the existing call has a `user_data` key-value pair with the same key as specified in the request, T-Server replaces that value with a new value, as shown in the following table.

Example of Update to User_Data

Existing user_data	user_data to Be Added	Result
<code>data1=1234 data2=5678</code> <code>data3=9012</code>	<code>data3=9999 data4=1212</code> <code>data5=5555</code>	<code>data1=1234 data2=5678</code> <code>data3=9999 data4=1212</code> <code>data5=5555</code>