

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Reporting and Analytics Aggregates Physical Data Model for a PostgreSQL Database

Table AGT SDR ACTIVITY HOUR

Table AGT SDR ACTIVITY HOUR

Description

Introduced: 8.5.0

In partitioned databases, this table is not partitioned.

This table contains a record of the activities that the user encountered while the call was being processed by the Application. A new row is added for each activity. The same columns and column descriptions apply to other AGT SDR ACTIVITY * tables.

Tip

- This document shows *table* information because it is more informative than *view* information. However, directly querying tables is not supported; perform your queries on views.
- This document shows the HOUR structure for each table, as an example. For each table, the same structure is used for SUBHR through YEAR views.
- Where referenced, IRF resources include:
 - Handling resources (such as self-service IVR ports, agents, or non-agent-associated DNs)
 - Mediation resources (such as a non-self-service IVR ports, voice treatment ports, ACD queues, routing points, and so forth) where the interaction ends in mediation before being distributed to a handling resource.
- IRF is an abbreviation for the INTERACTION_RESOURCE_FACT table.
- MSF is an abbreviation for the MEDIATION SEGMENT FACT table.

Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types

and descriptions for all columns in this table: Download a CSV file.

Hint: For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

Column List

Legend

Column	Data Type	Р	M	F	DV
DATE_TIME_KEY	integer			X	-1
SDR_ACTIVITY_KI	E Y nteger				-1
COMPLETED	integer				-1
SDR_CALL_DISPO)Sittlegte <u>r</u> KEY			X	-1
ACTIVITIES	integer				-1
DURATION	integer				-1
AGR_SET_KEY	integer		X	X	

DATE TIME KEY

Introduced: Release 9.0.011

The surrogate key that is used to join this aggregate table to the DATE_TIME dimension table to identify the calendar date and 15-minute interval at which the caller's participation in the interaction began.

SDR_ACTIVITY_KEY

The surrogate key that is used to join the SDR ACTIVITY dimension to the fact tables.

COMPLETED

Introduced: Release 9.0.011

The total number of activities that were completed during the reporting interval.

SDR CALL DISPOSITION KEY

Introduced: Release 9.0.011

The key that is used to join the SDR CALL DISPOSITION dimension to the fact tables.

ACTIVITIES

Introduced: Release 9.0.011

The total number of activities that began during the reporting interval.

DURATION

Introduced: Release 9.0.011

The total amount of time (in seconds) spent in Designer applications during the reporting period.

AGR_SET_KEY

The surrogate key that is used to join this aggregate table to the AGR_SET table.

Subject Areas

No subject area information available.