



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Microsoft Skype for Business Deployment Guide

Hiding Sensitive Data

5/4/2025

Hiding Sensitive Data

Contents

- **1 Hiding Sensitive Data**
 - 1.1 T-Library messaging
 - 1.2 CTI Message Headers

T-Server and Connector for Skype for Business components can print customer sensitive information in log files in:

- CTI link messages (both components)
- T-Library messaging (T-Server component)
- Specific debug information added for troubleshooting

The sensitive content includes:

- User Data in T-Events
- Content of Collected Digits
- Instant messages
- Treatment prompts

T-Library messaging

The option that controls whether potentially sensitive data is printed in the T-Server log file is `hide-sensitive-data`, which is configured in the **[TServer]** section of the T-Server Application. The default value of this option is `true`, meaning that the following sensitive data will be hidden in the T-Server log file:

- `AttributeCollectedDigits`, `AttributeLastDigit`, `AttributeDTMFDigits`, `AttributeTreatmentParms` will be hidden in T-Library requests and events.
- The headers “Data” and “Treatment-Params” will be hidden in CTI link messages. Instead of printing the actual data transmitted between T-Server and Connector, the log file will contain a string: `**** (length:nn)`, where `nn` is the length of the original data.

This feature can be disabled by setting the option value to `false`.

CTI Message Headers

The CTI messages used by T-Server and Connector contain various Microsoft Lync TServer Protocol (MLTP) message headers. The Connector can be configured with a list of MLTP message headers that might contain potentially sensitive data and should not be printed in the log file. Instead of printing the actual data transmitted between T-Server and Connector, the log file will contain a string: `**** (length:nn)`, where `nn` is the length of the original data.

To hide message headers, in the Annex tab of the **Switch** configuration object, in the **[log]** section, set the **hide-header** option to a comma-separated list of MLTP message headers that must not be printed in the log file.

For example:

```
[mslync] handle MLTP message
PARTY_CREATED * MLTP/1.0
media: voice
from: sip:user1@domain.com
to: sip:user21@domain.com
party-state: ALERTING
```

If **hide-header**=media,from,to,party-state, the following would be printed instead in the log file:

```
[mslync] handle MLTP message  
PARTY_CREATED * MLTP/1.0  
media: **** (length:5)  
from: **** (length:21)  
to: **** (length:21)  
party-state: **** (length:8)
```