

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

CSTA Connector for BroadSoft BroadWorks Deployment Guide

Treatments

Treatments

The CSTA Play Message request is mapped into a BroadWorks Treatment request as described in the following table:

Mapping of the BroadWorks Treatment Request to the CSTA PlayMessage Request

| BroadWorks Request | Parameters | CSTA PlayMessage Parameter |
|--------------------------------|-------------|------------------------------|
| RoutePointPlayBusyRequest | | Message ID = θ (zero) |
| | duration | Duration |
| | busyPattern | Extension busyPattern |
| RoutePointPlayMOHRequest | | Message ID = 1 |
| | duration | Duration |
| | digitMap | Extension collectDigits |
| RoutePointPlayRingbackRequest | | Message ID = 2 |
| | duration | Duration |
| | digitMap | Extension collectDigits |
| RoutePointPlaySilenceRequest | | Message ID = 3 |
| | duration | Duration |
| | digitMap | Extension collectDigits |
| RoutePointPlayTreatmentRequest | | Message ID = 4 |
| | duration | Duration |

| BroadWorks Request | Parameters | CSTA PlayMessage Parameter |
|---------------------------|--------------|----------------------------|
| | digitMap | Extension collectDigits |
| | audioUrlList | Extension audioUrl |
| | videoUrlList | Extension videoUrl |