



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server for CSTA Connector Deployment Guide

[Related Configuration Options](#)

12/15/2025

Related Configuration Options

The following configuration option supports the Smart OtherDN Handling feature:

convert-other-dn

convert-otherdn

Default Value: +agentid +reserveddn +fwd

Valid Values:

- +/-agentid—Turns on/off either the conversion of the Agent ID value provided in the OtherDN attribute to the DN associated with this Agent, or the DN value to Agent ID value (where appropriate).
- +/-reserveddn—Turns on/off the conversion of the OtherDN attribute for reserved DNs.
- +/-fwd—Turns on/off conversion of the OtherDN attribute in the TSetCallForward request.

Changes Take Effect: Immediately

Related Feature: **Smart OtherDN Handling**

Defines whether T-Server has to convert, if applicable, the value provided in the request's AttributeOtherDN attribute.

dn-for-undesired-calls

dn-for-undesired-calls

Default Value: No default value

Valid Values: Any valid switch DN

Changes Take Effect: Immediately

Related Feature: **Smart OtherDN Handling**

Specifies the DN that T-Server uses as the request destination if the client provides a reserved DN in the request.

Note: You can set a value for this option in the appropriate DN Annex tab in the TServer section. When set there, this value overrides the default value for the DN.