



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server for Cisco UCM Deployment Guide

Agent state change on unavailable DN

12/16/2025

Agent state change on unavailable DN

A call routed to an agent on an unexpectedly unavailable DN could be continuously routed to that same agent. To avoid this scenario, and to avoid further routing to that out-of-service DN, you can set the agent state to Not Ready, Walkaway, or Logged Out.

You can enable this functionality in any of three ways, in order of precedence:

- For specific calls, specify the extensions key `INVALID_DEST_ACTION`, with a value of `notready`, `walkaway`, or `logout`, in the `RequestRouteCall`.
- For specific agents, set the option **route-invalid-dest-action** in the Tserver section of the Annex tab of DN objects.
- For all agents, set the option **route-invalid-dest-action** in the Tserver section of the application.

route-invalid-dest-action

Valid Values: *none*, *notready*, *walkaway*, *logout*

Default: *none*

Effective: Immediately

When T-Server receives the error code `TERR_INV_DEST_DN` (177) when it tries to route a call, it takes one of these actions:

- *none*: T-Server takes no action.
- *notready*: T-Server sets the agent to `NotReady`.
- *walkaway*: T-Server sets the agent to `NotReady` with work mode `Walkaway`.
- *logout*: T-Server sets the agent to `LoggedOut`.

This option does not apply when DND is enabled.