



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Workforce Management ETL Database Reference

Dimension Tables

5/5/2025

# Dimension Tables

This topic describes the Dimension tables in the Workforce Management (WFM) ETL Database schema. To view the details in each table click the table name in the first column. For example, WFM\_BU or WFM\_SITE.

For a description of the abbreviations used in these tables, see [Abbreviations for ETL Database Terms](#).

## WFM\_BU

This table contains business unit descriptive information.

Column	Data type	P	M	F	DV
WFM_BU_KEY	int	X	X		
WFM_BU_NAME	varchar(255)		X		
WFM_TIMESTAMP	numeric(19)		X		
TIME_ZONE_KEY	int			X	
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

## Description of Columns

- **WFM\_BU\_KEY**—The primary key for this table.
- **WFM\_BU\_NAME**—The name of Business Unit (BU).
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **TIME\_ZONE\_KEY**—The surrogate key used to join the TIME\_ZONE dimension to the fact tables. It specifies the time zone of the Business Unit.
- **ACTIVE\_FLAG**—Indicates whether the Business Unit is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).

- **PURGE\_FLAG**—This field is reserved.

## WFM\_SITE

This table contains site descriptive information.

Column	Data type	P	M	F	DV
WFM_SITE_KEY	int		X		
WFM_BU_KEY	int		X	X	
WFM_SITE_NAME	varchar(255)		X		
WFM_TIMESTAMP	numeric(19)		X		
SWITCH_KEY	int			X	
TIME_ZONE_KEY	int			X	
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

### Description of Columns

- **WFM\_SITE\_KEY**—The primary key for this table.
- **WFM\_BU\_KEY**—The surrogate key used to join the WFM\_BU dimension to the fact tables. It specifies the Business Unit of the Site.
- **WFM\_SITE\_NAME**—The name of the Site.
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **SWITCH\_KEY**—The surrogate key used to join the GIDB\_GC\_SWITCH dimension to the fact tables. It specifies the switch associated with the Site.
- **TIME\_ZONE\_KEY**—The surrogate key used to join the TIME\_ZONE dimension to the fact tables. It specifies the time zone of the Site.
- **ACTIVE\_FLAG**—Indicates whether the Site is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).
- **PURGE\_FLAG**—This field is reserved.

## WFM\_TEAM

This table contains team descriptive information.

Column	Data type	P	M	F	DV
WFM_TEAM_KEY	int	X	X		
WFM_TEAM_NAME	varchar(255)		X		
WFM_SITE_KEY	int		X	X	
WFM_TIMESTAMP	numeric(19)		X		
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

### Description of Columns

- **WFM\_TEAM\_KEY**—The primary key for this table.
- **WFM\_TEAM\_NAME**—The name of the Team.
- **WFM\_SITE\_KEY**—The surrogate key used to join the WFM\_SITE dimension to the fact tables. It specifies the Site of the Team.
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **ACTIVE\_FLAG**—Indicates whether the Team is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).
- **PURGE\_FLAG**—This field is reserved.

## WFM\_AGENT

This table contains agent descriptive information.

Column	Data type	P	M	F	DV
WFM_AGENT_KEY	int	X	X		
WFM_BU_KEY	int			X	

Column	Data type	P	M	F	DV
WFM_SITE_KEY	int			X	
WFM_TEAM_KEY	int			X	
EMPLOYEE_ID	varchar(64)		X		
FIRST_NAME	varchar(64)		X		
LAST_NAME	varchar(64)		X		
HIRE_DATE	date		X		
TERMINATION_DATE	date				
WFM_TIMESTAMP	numeric(19)		X		
AGENT_KEY	int			X	
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

## Description of Columns

- **WFM\_AGENT\_KEY**—The primary key for this table.
- **WFM\_BU\_KEY**—The surrogate key used to join the WFM\_BU dimension to the fact tables. It specifies the Agent's business unit.
- **WFM\_SITE\_KEY**—The surrogate key used to join the WFM\_SITE dimension to the fact tables. It specifies the Agent's site.
- **WFM\_TEAM\_KEY**—The surrogate key used to join the WFM\_TEAM dimension to the fact tables. It specifies the Agent's team. It is NULL if Agent does not belong to any team.
- **EMPLOYEE\_ID**—The Agent's employee ID.
- **FIRST\_NAME**—The Agent's first name.
- **LAST\_NAME**—The Agent's last name.
- **HIRE\_DATE**—The Agent's hire date.
- **TERMINATION\_DATE**—The Agent's termination date.
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **AGENT\_KEY**—The surrogate key used to join the GIDB\_GC\_AGENT dimension to the fact tables.
- **ACTIVE\_FLAG**—Indicates whether the agent is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application

Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).

- **PURGE\_FLAG**—This field is reserved.

## WFM\_ACTIVITY\_TYPE

This table contains activity types and descriptions.

Column	Data type	P	M	F	DV
WFM_ACTIVITY_TYPE_KEY	int	X	X		
WFM_ACTIVITY_TYPE_NAME	varchar(64)		X		

### Description of Columns

- **WFM\_ACTIVITY\_TYPE\_KEY**—The Activity type ID.
- **WFM\_ACTIVITY\_TYPE\_NAME**—The Activity type name. The table below contains valid values.

ID	Name
0	'Immediate'
2	'Fixed Staffing'
4	'Deferred'
10	'Activity Group'

## WFM\_ACTIVITY

This table contains activity descriptive information.

Column	Data type	P	M	F	DV
WFM_ACTIVITY_KEY	int	X	X		
WFM_BU_KEY	int		X	X	
WFM_SITE_KEY	int			X	
WFM_MSA_KEY	int			X	
WFM_ACTIVITY_NAME	varchar(255)		X		
WFM_ACTIVITY_SHORT_NAME	varchar(6)		X		
WFM_ACTIVITY_TYPE_KEY	int		X	X	
WFM_TIMESTAMP	numeric(19)		X		
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	

Column	Data type	P	M	F	DV
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

## Description of Columns

- **WFM\_ACTIVITY\_KEY**—The primary key for this table.
- **WFM\_BU\_KEY**—The surrogate key used to join the WFM\_BU dimension to the fact tables. It specifies the Business Unit of the Activity.
- **WFM\_SITE\_KEY**—The surrogate key used to join the WFM\_SITE dimension to the fact tables. It specifies the Site of the Activity. It is NULL if Activity is Multi-Site Activity (MSA) or Activity Group (AG).
- **WFM\_MSA\_KEY**—The surrogate key used to join the parent Multi-Site Activity to the child Activity. It is NULL for Multi-Site Activity and Activity Group or if Activity does not belong to any Multi-Site Activity.
- **WFM\_ACTIVITY\_NAME**—The name of the Activity.
- **WFM\_ACTIVITY\_SHORT\_NAME**—The short name of the Activity.
- **WFM\_ACTIVITY\_TYPE\_KEY**—The surrogate key used to join the WFM\_ACTIVITY\_TYPE dimension. It specifies the type of the Activity.
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **ACTIVE\_FLAG**—Indicates whether the Activity is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).
- **PURGE\_FLAG**—This field is reserved.

## WFM\_SSG\_TYPE

This table contains schedule state group types and descriptions.

Column	Data type	P	M	F	DV
WFM_SSG_TYPE_KEY	int	X	X		
WFM_SSG_TYPE_NAME	nchar(64)		X		

## Description of Columns

- **WFM\_SSG\_TYPE\_KEY**—The Schedule State Group type ID.

- **WFM\_SSG\_TYPE\_NAME**—The Schedule State Group type name. The table below contains valid values.

ID	Name
1	'Working Overhead'
2	'Non-Working Overhead'
3	'Actual Work'

## WFM\_SSG

This table contains schedule state group descriptive information.

Column	Data type	P	M	F	DV
WFM_SSG_KEY	int	X	X		
WFM_SITE_KEY	int		X	X	
WFM_SSG_NAME	varchar(255)		X		
WFM_SSG_TYPE_KEY	int		X	X	
WFM_SSG_WEIGHT	int		X		
WFM_TIMESTAMP	numeric(19)		X		
ACTIVE_FLAG	int		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric(19)			X	
UPDATE_AUDIT_KEY	numeric(19)				
PURGE_FLAG	int				

## Description of Columns

- **WFM\_SSG\_KEY**—The primary key for this table.
- **WFM\_SITE\_KEY**—\*The surrogate key used to join the WFM\_SITE dimension to the fact tables. It specifies the site of the Schedule State Group (SSG).
- **WFM\_SSG\_NAME**—The name of the Schedule State Group.
- **WFM\_SSG\_TYPE\_KEY**—The surrogate key used to join the WFM\_SSG\_TYPE dimension. It specifies the type of the Schedule State Group.
- **WFM\_SSG\_WEIGHT**—The superficial weight value of Schedule State Group used for grouping.
- **WFM\_TIMESTAMP**—An internal timestamp value.
- **ACTIVE\_FLAG**—Indicates whether the Schedule State Group is currently active: 0 = No, 1 = Yes.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, enterprise application integration (EAI), and ETL tools (that is, applications that need to identify newly added data).



- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).
- **PURGE\_FLAG**—This field is reserved.

## WFM\_STATE\_TYPE

This table contains schedule state types and descriptions.

Column	Data type	P	M	F	DV
WFM_STATE_TYPE_KEY	int	X	X		
WFM_STATE_TYPE_NAME	varchar(64)		X		

### Description of Columns

- **WFM\_STATE\_TYPE\_KEY**—The State type ID.
- **WFM\_STATE\_TYPE\_NAME**—The State type name. The table below contains valid values.

ID	Name
0	'None'
1	'Day Off'
2	'Time Off'
3	'Exception'
4	'Break'
5	'Meal'
6	'Activity'
7	'Activity Set'
8	'Shift'
9	'Marked Time'

## WFM\_STATE

This table contains schedule state descriptive information.

Column	Data type	P	M	F	DV
WFM_STATE_KEY	int	X	X		
WFM_SITE_KEY	int		X	X	

Column	Data type	P	M	F	DV
WFM_SSG_KEY	int			X	
WFM_STATE_TYPE_KEY	int		X	X	
WFM_STATE_ID	int		X		
WFM_STATE_NAME	varchar(255)		X		
WFM_STATE_SHORT_NAME	varchar(6)		X		
TENANT_KEY	int			X	
CREATE_AUDIT_KEY	numeric (19)			X	
UPDATE_AUDIT_KEY	numeric(19)			X	
PURGE_FLAG	int				

## Description of Columns

- **WFM\_STATE\_KEY**—The primary key for this table.
- **WFM\_SITE\_KEY**—The surrogate key used to join the WFM\_SITE dimension to the fact tables. It specifies the Site of the Schedule State.
- **WFM\_SSG\_KEY**—The surrogate key used to join the WFM\_SSG dimension to the fact tables. It specifies the SSG of the Schedule State.
- **WFM\_STATE\_TYPE\_KEY**—The surrogate key used to join the WFM\_STATE\_TYPE dimension. It specifies the type of the Schedule State.
- **WFM\_STATE\_ID**—The ID of Schedule State corresponding to the type of Schedule State. The ID is unique within the context of Schedule State type.
- **WFM\_STATE\_NAME**—The name of the Schedule State.
- **WFM\_STATE\_SHORT\_NAME**—The short name of the Schedule State.
- **TENANT\_KEY**—The surrogate key used to join the TENANT dimension to the fact tables.
- **CREATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify newly added data).
- **UPDATE\_AUDIT\_KEY**—The surrogate key used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value is useful for aggregation, Enterprise Application Integration (EAI), and ETL tools (that is, applications that need to identify recently modified data).
- **PURGE\_FLAG**—This field is reserved.

## WFM\_PERF\_ITEM

This table contains performance items (statistics) and descriptions.

Column	Data type	P	M	F	DV
WFM_PERF_ITEM_KEY	int	X	X		
WFM_PERF_ITEM_CODE	varchar(64)		X		

Column	Data type	P	M	F	DV
WFM_PERF_ITEM_DESCRIPTION	VARCHAR(255)		X		

## Description of Columns

- **WFM\_PERF\_ITEM\_KEY**—The Performance item ID.
- **WFM\_PERF\_ITEM\_CODE**—The code of Performance item (statistic). The table below contains WFM Performance statistics.
- **WFM\_PERF\_ITEM\_DESCRIPTION**—The description of the Performance item.

## Performance Statistics

ID	Code	Description
12	FRC_CALC_STAFFING	Total Calculated Staffing Difference (between Optimal number of agents for Forecast workload and Calculated Staffing)
16	FRC_REQ_STAFFING	Total Required Staffing
38	FRC_CALC_SERVICE_PCT	Weighted average of (Achieved) Calculated Service Level % (weighted on Forecast Interaction Volume)
15	FRC_REQ_SERVICE_PCT	Weighted average of (Achieved) Required Service Level % (weighted on Forecast Interaction Volume) for Activity of type Deferred
40	FRC_CALC_ASA	Weighted average of (Achieved) Calculated Average Speed of Answer (weighted on Forecast Interaction Volume)
14	FRC_REQ_ASA	Weighted average of Required Average Speed of Answer (weighted on Forecast Interaction Volume)
39	FRC_CALC_ABANDONED_IV_PCT	Weighted average of (Achieved) Calculated Abandoned Interaction Volume % (weighted on Forecast Interaction Volume)
18	FRC_REQ_ABANDONED_IV_PCT	Weighted average of Required Abandoned Interaction Volume % (weighted on Forecast Interaction Volume)
41	FRC_CALC_MAX_OCCUPANCY_PCT	Weighted average of (Achieved) Calculated Maximum Occupancy % (weighted on Forecast Interaction Volume)

ID	Code	Description
77	FRC_REQ_MAX_OCCUPANCY_PCT	Weighted average of Required Maximum Occupancy % (weighted on Forecast Interaction Volume)
10	FRC_IV	Total of Forecast Interaction Volume
50	FRC_CALC_FTE	Total of Calculated Full-time Equivalent
51	FRC_REQ_FTE	Total of Required Full-time Equivalent
56	FRC_CALC_MAN_HOURS	Total of Calculated Man Hours
57	FRC_REQ_MAN_HOURS	Total of Required Man Hours
21	SCH_COVERAGE	Total of Scheduled Coverage
24	SCH_SERVICE_PCT	Weighted average of Scheduled Service Level % (weighted on Forecast Interaction Volume)
19	SCH_ASA	Weighted average of Scheduled Average Speed of Answer (weighted on Forecast Interaction Volume)
22	SCH_ABANDONED_IV_PCT	Weighted average of Scheduled Abandoned Interaction Volume % (weighted on Forecast Interaction Volume)
23	SCH_MAX_OCCUPANCY_PCT	Weighted average of Scheduled Maximum Occupancy % (weighted on Forecast Interaction Volume)
49	SCH_FTE	Total of Scheduled Full-time Equivalent
55	SCH_MAN_HOURS	Total of Scheduled Man Hours
6	ACT_STAFFING	Total of Actual Staffing Difference (between Optimal number of agents for Actual workload and Scheduled Coverage)
59	ACT_COVERAGE	Total of Actual Coverage (agent minutes divided by timestep)
3	ACT_SERVICE_PCT	Weighted average of Actual Service Level % (weighted on Actual Distributed Interaction Volume) for Activity of type Deferred
5	ACT_ASA	Weighted average of Actual Average Speed of Answer (weighted on Actual Interaction Volume)
4	ACT_ABANDONED_IV_PCT	Total of Actual Abandoned

ID	Code	Description
		Interaction Volume %
1	ACT_IV	Total of Actual Interaction Volume
62	ACT_ABANDONED_IV	Total of Actual Abandoned Interaction Volume %
8	ACT_DISTRIBUTED_IV	Total of Actual Distributed Interaction Volume
9	ACT_HANDLED_IV	Total of Actual Handled Interaction Volume
60	ACT_FTE	Total of Actual Full-time Equivalent
61	ACT_MAN_HOURS	Total of Actual Man Hours
20	SCH_HEADCOUNT	Total of Scheduled Headcount
2	ACT_AHT	Weighted average of Actual Handle Time (weighted on Actual Handled Interaction Volume)
78	ACT_SIMPLE_AHT	Simple average of Actual Handle Time
11	FRC_AHT	Weighted average of Forecast Handle Time (weighted on Forecast Interaction Volume)
58	FRC_SIMPLE_AHT	Simple average of Forecast Average Handle Time
70	SCH_AHT	Weighted average of Scheduled Average Handle Time (weighted on Forecast Interaction Volume)
69	SCH_IV	Total of Scheduled Interaction Volume